


SIDE ENTRY 2-PORT MODULAR PCB JACK 8P PROFILE=13.60MM (FULLY SHIELDED)

SPECIFICATIONS

Insulation Resistance: 500MΩ Min.
Contact Resistance: 20mΩ Max.
Rating Current: 1.5A Max.
Rating Voltage: 120V AC.
Dielectric Voltage: 1000 Vrms 60 Sec. Min.
Temperature Range: -40°C / +85°C
Durability: 500 Mating cycles Min.

MATERIALS

Housing: PBT Glass Filled (UL 94V-0)
Soldering Temperature: 235°C
Color: Black
Spring Wire: Phosphor Bronze
 Gold plating Over Nickel
Shield: Brass plating Nickel Alloy
All materials must be RoHS compliant.



ORDERING INFORMATION:

P/N M J $\frac{x}{1}$ - $\frac{x}{2}$ $\frac{x}{3}$ B $\frac{0}{4}$

1. CATEGORY TYPE:
 "1H" CAT. 3
 "Y1" CAT. 5
2. NO. OF POSITIONS & CONTACTS:
 "88" 8P8C
3. CONTACT FINISH:
 "A" 6 MICROINCH GOLD
 "B" 15 MICROINCH GOLD
 "C" 30 MICROINCH GOLD
 "D" 50 MICROINCH GOLD
4. NO. OF PORTS:
 02

NOTE: WITH TOP PANEL GROUNDS

